

Common Dimensions for Braided Packing - Acrylic Gland Packing

Туре	Standard Diameter (mm)	Cross-Section (mm)	Length per Roll (m)	Customization Options
Acrylic Fiber Gland Packing	3, 6, 9, 12	3x3, 6x6, 9x9	10 - 50	Fiber density adjustments
PTFE-Coated Acrylic Gland Packing	4, 8, 10, 14	4x4, 8x8, 10x10	5 - 30	PTFE content modifications
High-Temperature Acrylic Packing	5, 10, 15	5x5, 10x10, 15x15	8 - 40	Graphite reinforcement ratio customization
Corrosion-Resistant Acrylic Packing	3, 7, 11	3x3, 7x7, 11x11	10 - 25	Silicone blend thickness adjustments
Reinforced Acrylic Braided Packing	6, 12, 18	6x6, 12x12, 18x18	10 - 50	Hybrid fiber ratio customization



Common Dimensions for Braided Packing - Aramid Packing

- 3						
	Туре	Standard Diameter (mm)	Cross-Section (mm)	Length per Roll (m)	Customization Options	
	Aramid Fiber Packing	3, 6, 8, 10	3x3, 6x6, 8x8	10 - 50	Custom diameters, fiber density adjustments	
	Aramid Fiber Compression Gland Packing	5, 8, 12, 15	5x5, 8x8, 12x12	5 - 30	PTFE content adjustments	
	Aramid Braided Packing for Auto Water Pump Seal	4, 6, 9	4x4, 6x6, 9x9	8 - 20	Silicone coating thickness customization	
	Pump and Valve Compression Gland Packing	6, 10, 16	6x6, 10x10, 16x16	10 - 40	Graphite ratio modifications	
	Aramid Fiber PTFE Packing	3, 5, 8, 12	3x3, 5x5, 8x8	15 - 60	PTFE layer thickness customization	
	Wear Resistance Aramid Fiber Gland Packing	5, 9, 14	5x5, 9x9, 14x14	10 - 30	Carbon fiber hybridization options	
	Kevlar Gland Packing	8, 12, 18	8x8, 12x12, 18x18	5 - 25	Binder type adjustments (e.g., epoxy, resin)	
	Oil Immersed Aramid Packing	3, 5, 7	3x3, 5x5, 7x7	3 - 15	Oil/graphite blend ratio customization	



20MO	hull	ashui "	Hengsh	ui Hongwo Technology
Common Dimensions for Braide	d Packing - <u>Carbon F</u>	iber Gland Packing		
Туре	Standard Diameter (mm)	Cross-Section (mm)	Length per Roll (m)	Customization Options
Carbon Fiber Gland Packing for Pumps	3, 6, 8, 10	3x3, 6x6, 8x8	5 - 30	Tailored diameters, binder adjustments
Carbon Fiber Gland Packing with Graphite	5, 8, 12, 16	5x5, 8x8, 12x12	10 - 50	Graphite density, foil thickness
Graphite Carbon Fiber Packing	4, 6, 10, 15	4x4, 6x6, 10x10	15 - 60	Pre-compressed forms, expanded graphite layers
High Pressure Carbon Fiber Braided Packing	8, 10, 12, 20	8x8, 10x10, 12x12	5 - 25	Hybrid reinforcement (e.g., aramid)
Corrosion Resistance Carbon Fiber Braided Packing	3, 5, 8, 10	3x3, 5x5, 8x8	10 - 40	Polymer matrix modifications
Carbon Fiber Compression Braided Packing	4, 7, 9, 12	4x4, 7x7, 9x9	8 - 20	Lubricant type, braiding tightness
Packing	4, 7, 9, 12		Henos	



45hull 1

	awo shi		chui do	Uanashui Uan	anna Tashmalaan
Y	Common Dimensions for Braided Page	cking - <u>Graphite Packi</u>	ng	Hengshul Hor	ngwo Technology
	Туре	Standard Diameter (mm)	Cross-Section (mm)	Length per Roll (m)	Customization Availability
	Expanded Graphite Gland Packing	3, 6, 10, 15	3x3, 6x6, 10x10	10 - 50	Yes (Density Adjustable)
	High Pressure Mechanical Seal Graphite Gland Packing	5, 8, 12, 20	5x5, 8x8, 12x12	5 - 30	Yes (Reinforcement Modifiable)
	Flexible Graphite Gland Packing	2, 4, 8, 12	2x2, 4x4, 8x8	15 - 60	Yes (Foil Thickness Custom)
	Cotton Packing with Graphite	4, 6, 10	4x4, 6x6, 10x10	5 - 20	Yes (Graphite Ratio Adjustable)
	Cotton Packing with Oil	3, 5, 8	3x3, 5x5, 8x8	3 - 15	Yes (Oil Type Customizable)
	Jenoshui Honov	enoshuiH	nomo	enoshuil	Houd



Common Dimensions for Braided Packing - Phenolic Packing

	Туре	Standard Diameter (mm)	Cross-Section (mm)	Length per Roll (m)	Customization Options
	Phenolic Fiber Impregnated with PTFE Braided Gland Packing for Pump	3, 6, 8, 12	3x3, 6x6, 8x8	10 - 50	PTFE content adjustments, braid patterns
	Phenolic Gland Packing for Pumps and Valves	4, 7, 10, 14	4x4, 7x7, 10x10	5 - 30	Fiber density modifications
	Kynol Fiber Gland Packing	5, 9, 13, 18	5x5, 9x9, 13x13	8 - 25	Thermal resistance enhancements
	Compression Phenolic Fiber Packing	6, 10, 15	6x6, 10x10, 15x15	10 - 40	Graphite blend ratio customization
•	Heudz	rendshir		Helio	



Common Dimensions for Braided Packin		He	ngshui Hongv	wo Technology
Туре	Standard Diameter (mm)	Cross-Section (mm)	Length per Roll (m)	Customization Availability
Aramid Fiber PTFE Packing	3, 6, 8, 10, 12	3x3, 6x6, 10x10	10 - 50	Yes (Cut-to-Length)
Non Asbestos PTFE Packing with Oil	4, 5, 8, 12	4x4, 5x5, 8x8	5 - 30	Yes (Oil Type Adjustable)
White PTFE Gland Packing with Aramid Corners	5, 8, 10, 15	5x5, 8x8, 10x10	10 - 100	Yes (Aramid Density Custom)
Black Graphite PTFE Gland Packing with Aramid Corners	6, 9, 12, 16	6x6, 9x9, 12x12	20 - 60	Yes (Graphite Content Adjust)
High-Temperature PTFE Graphite Gland Packing	5, 10, 15, 20	5x5, 10x10, 15x15	15 - 50	Yes (Pre-Compressed Forms)
PTFE with Aramid in Corners Reinforced Braided Sealing Packing	4, 6, 8, 12	4x4, 6x6, 8x8	10 - 40	Yes (Braiding Pattern Adjust)
Wear Resistance PTFE Packing	5, 8, 12, 18	5x5, 8x8, 12x12	10 - 30	Yes (Reinforcement Ratio Mod)
Pure PTFE Pump Gland Braided Packing Without Oil	3, 5, 8, 10	3x3, 5x5, 8x8	5 - 25	Yes (FDA-Compliant Options)



	awo shui		huil elle	Jenashui Hor	ngwo Technology
1	Common Dimensions for Braided Packin	ng - <u>Ramie Gland Pa</u>		Tengshar Hor	igwo recimotogy
	Туре	Standard Diameter (mm)	Cross-Section (mm)	Length per Roll (m)	Customization Options
	Ramie Fiber Packing with PTFE Lubricant	3, 6, 9, 12	3x3, 6x6, 9x9	10 - 50	PTFE concentration adjustments
	Mechanical Seal Compression Ramie Fiber Gland Packing	4, 8, 10, 14	4x4, 8x8, 10x10	5 - 25	Silicone binder density modifications
	Corrosion-Resistant & High-Temperature Ramie Fiber Gland Packing	5, 10, 15	5x5, 10x10, 15x15	8 - 30	Graphite layer thickness customization
	High Pressure Tearing-Resistant Flax Packing	6, 12, 18	6x6, 12x12, 18x18	10 - 40	Hybrid fiber ratio adjustments
	Flax Ramie Gland Packing	3, 5, 7, 10	3x3, 5x5, 7x7	3 - 15	Wax coating intensity customization
	House		ONIC		Hollis
		140		Shull	
	Henoshuillo	dell'		endshui	
	He	noshui Ho		7	